Project Description:
Renovate building interior. No site work other than driveway work at new south side foundation and apparatus bay.

Site area:

Local Jurisdiction:
United States Forest Service

Zone classification:
Not applicable (Federal land).

Applicable building code:
Oregon State Structural Specialty Code (latest edition)

Occupancy classification:
R-2 / S-1 / B. Mixed-use, non-separated.

Construction Type:
V-B, sprinklered to NFPA13. Currently the building is not fire sprinklered but will be as part of this project.

Building Height:
Allowable (OSSC): 1 story, 40 feet (Basic based on non-separated occupancy (S-1 sets limit)) / 2 stories, 50' (Sprinklered).

Building setbacks:
Front (street side): 10'
Side, rear: None.

Total building area:
3266 square feet.

Allowable floor area:
7000 square feet (limit set by R-2 occupancy).

Required separations:
Between dwelling unit and S-1 = 1/2 Hr. Between dwelling unit and B = 1/2 Hr. (420.2, 708.3 Ex. 2).
Between S-1 and B = 0-Hr.

Occupant load:
29 (See Code Plan).

Exits:
Distance to Exit before two exits are required:
B and S occ. max. = 100', actual = 96' (Sprinklered)
R-2 occ. max. = 125', actual 53'. Therefore CPET not applicable. (T1014.3)

Single exit floor travel distance max. w/sprinkers: B = 100' S-1 = 100' (T1021.2(2)), actual = 96'
R-2 (dwelling unit) w/sprinklered = 125' (T1021.2(1)), actual = 53'.

Egress lighting not required (1006.3.2).

Corridor Rating:
R, B and S occ.: Non-rated under quantity of occupants listed in (T1018.1).

Plumbing Fixtures:
R-2: (dwelling unit): Self-contained.
B and S occupancy: Toilet 1 per 25 occ. = 1, Lavatory 1 per 40 occ. = 1

Barrier Removal (up to 25% of project cost):
When complete building will be accessible. Note that parking and access to the building are in the right-of-way.

Energy Code:
Building envelope fenestration
- Entrance door Min U = (Existing)
- New windows Min U = .35, Max SHGC = .40
- Rollup doors Min U = 0.50, Max SHGC = .40
New exterior wall (south) = R-21
Attic = (Existing)

No insulaton change to un-modified walls. Fill any exposed existing wall cavities with fiberglass batt insulation.

Sound transmission:
Air-borne between dwelling unit and other occupancies: STC of 50 or greater. This is a renovation project with no change in area, no change in occupancy, and no changes to the walls separating the occupancies. Therefore requirement is not applicable.
Structure-borne at floor-ceiling assemblies between dwelling unit and other occupanes: IIC of 50 or greater. Not applicable in a single-story building.

Barrier Removal Schedule:
Estimated project cost = $400,000
Renovation of 105 Toilet Rm. #2 = $25,000
Renovation of 114 Kitchen = $30,000
Installation of tactile signage = $4000
Total cost of barrier removal items = $59,000
Percentage of overall project = 15%

2 CODE REVIEW



1 CODE PLAN

1/4" = 1'-0"

NORTH

REGISTERED ARCHITECT BLAKE W. SCOTT PORTLAND, OREGON STATE OF OREGON

This document and the ideas and designs incorporated herein is an instrument of service of KEYSTONE Architecture Planning and Project Management. KEYSTONE retains all common law, statutory and other reserved rights, including copyright thereto. This document shall not be used in whole or in part for any other project without the express written authorization of KEYSTONE Architecture Planning and Project Management.

Government Camp Fire Station

Renovation - Rebid
Government Camp Loop Road
Government Camp, Oregon

KEYSTONE
ARCHITECTURE PLANNING
AND PROJECT MANAGEMENT
12010 SE IDLEMAN ROAD, PORTLAND, OR 97086
PHONE: (503) 761-1362 FAX: (503) 760-0934

REVISION	DATE

APPROVED: BWS
DRAWN BY:
SCALE: AS SHOWN
DATE: 12/9/17
JOB: 17-102
FILE:

A1.01

© KEYSTONE ARCHITECTURE